

## Bosal P4 thin walled exchangers for 400 – 1000°C / 750 – 1832°F

BOSAL Energy offers welded, compact plate heat exchangers for high temperature applications. The heat exchanger line is modular, and is available in high-end stainless steel or Inconel. They are highly effective and are suitable for high temperature (up to 1,000°C/ 1,832°F) with limited Cr evaporation and metal dusting.

### Application

Suitable for a wide range of applications, such as:


- Fuel cell systems (SOFC, PEMFC, MCFC)
- Chemical Processes
- Gas turbines
- Micro turbines
- Stirling engines
- Internal combustion engines

### Benefits


- Compact,
- Easy to install
- Designed for >40,000 field operating hours
- Inconel version for optimal chemical resistance
- Catalytic coating available for combined heat exchange and steam reforming

### Design

- Secured quality with robotized welding (Laser, TIG, SP-Mag)
- Validation tested using highly sophisticated infrastructure
- Manufacturing and process engineering expertise




Schematics of the hot and cold flow direction



Boundary conditions: Air-air,  $\dot{m}_{cold} = \dot{m}_{hot}$ ,  $T_{cold,in} = 20\text{ }^{\circ}\text{C}$ ,  $T_{hot,in} = 800\text{ }^{\circ}\text{C}$ ,  $p_{cold} = p_{hot} = 1\text{ bar}(a)$

Technical data		
Housing material	Stainless steel Inconel	
Foil material	Stainless steel Inconel (optional)	
Max. flowrate m <sup>3</sup> /h (gpm)	59 (260)	
Max. design temperature °C (°F)	900 (1652) 1000 (1832) (Inconel)	
Flow directions	Counter flow or co flow	
Oxidative coating (optional)	Heat exchanger with oxidizer function	
Reductive coating (optional)	Heat exchanger with Steam reformer function	
Dimensions and mass		
# plate pairs (= n)	A (height) mm (inches)	B (Port OD) mm (inches)
20	52 (2.05)	33.4 (1.23)
40	98 (3.86)	33.4 (1.23)
# plate pairs (= n)	Weight kg (lb)	Volume l (gal)
20	3.82 (8.35)	1.5 (0.41)
40	6.30 (13.75)	3.0 (0.82)



Boundary conditions: Air-air,  $\dot{m}_{cold} = \dot{m}_{hot}$ ,  
 $T_{cold_{in}} = 20\text{ }^{\circ}\text{C}$ ,  $T_{hot_{in}} = 800\text{ }^{\circ}\text{C}$ ,  $p_{cold} = p_{hot} = 1\text{ bar}(a)$

Dimensional Drawing  
mm (inches)

